

MySense: Sensor Kits

How Did They Do It



- ▶ **Measurement Data Exchange Format (MDEF first implementation)**
 - meta status information exchange
 - measurements data exchange
 - marshalling (data linearisation) in:
 - **JSON**
 - **Python pickle ?**

teus hagen

email: mysense@behouddeparel.nl



vereniging Behoud de Parel
<http://behouddeparel.nl>

measurement data exchange format

dream two



- ◆ **we all do data stream communication:**

(s)http post, json, xml, python pickle (security issue!)

- ◆ **lessons learned:**

timestamps, version, sensor type, data unit, meta data

(defaults, etc.), flexible, use of state?, human readable, sample


implementations, naming, independent, version, scalable,

more?

- ◆ **MySense data collector**

data acquisition, data check, monitoring and forwarder

Python data format how it is done



- ◆ **internal** modules interfaces

- ◆ data record **input** interface:

Mosquitto (MQTT), InfluxDB, backup data restore

- ◆ **database** interface MySQL

- ◆ data record **output** interface:

HTTP(s), Mosquitto, InfluxDB, monitor, debugging

JSON example (uses state, defaults)

```
{
  'meta': [ { 'id': '123456ABCDE',
              'label': 'BdP-1234',
              'GPS': [ 52.123456, 6.123456], // home static
              'match': { r'bme([26]80)': 'BME\1', r'temp.*': 'temperature'},
              'sensors': [ { 'BME280': { 'temp': 'C', 'RH': '%' }, } ]
            } ],
  'data': [ { 'date': 123456789,
              'BME280': { 'temperature': 21.3, 'pressure': 1023 },
              'SPS30': { 'date': 123456790, 'PM2.5 #': 23.4 },
              'GPS': [ 52.123454, 6.123454] // dynamic
            } ]
}
```

meta info configuration

names of 'pollutants'

```
♦ "translate": {  
  "pm25": {"pm25", "pm2.5", "PM2.5"},  
  "pm10": {"pm10", "pm", "PM"},  
  "O3": {"O3", "ozon"},  
  "temp": {"temp", "temperature"},  
  "ws": {"ws", "windspeed", "windsnelheid"},  
  "wr": {"wr", "windrichting", "winddirection", "direction"},  
  "geohash": {"geohash",},  
  "altitude": {"altitude", "alt", "hoogte", "height"},  
  "longitude": {"longitude", "long", "lon", "lengte graad"},  
  . . .
```

meta info information

default info sensor types

MySQL database table 'SensorTypes'

an example:

timestamp: 2021-11-07 15:25:39 CET

product: SDS011

matching: (SDS|sds)011 regular expression

producer: Nova

category: dust


fields: list of name, unit, calibration function (type [Taylor sequence]) . . .

pm25, ug/m3, PMSx003 [1.6190,1.5450] SPS30 [2.1630,0.7645] BAM1020 [5.7590,0.3769]

pm10, ug/m3, PMSx003 [3.7600,1.1570] SPS30 [1.6890,0.6322] BAM1020 [1.4370,0.4130]

Measurements Data Exchange Format

record envelope example



```
{ // MDEF data record envelope
```

```
// if timestamp, version, or id is not defined in data record  
// the key of child in the tree is taken.  
// timestamp default: timestamp of receive data
```

```
"version": 0.02, // version of exchange format Nov 2021  
"id": { "project": "SAN", "serial": "78CECEA5167524" },  
"timestamp": 1621862416, // or "2021-05-24T15:20+02:00",
```

```
// meta data is state information of a measurement kit
```

```
"meta": ...
```

```
"data": ...
```

```
"net": ...
```

```
}
```

Measurements Data Exchange Format

meta record example



// optional, meta data is state information of a measurement kit, default undefined

"meta": { // meta data (re)definitions, kit state sensor type in use definitions

"*version*": 0.2, // firmware version, optional

"*timestamp*": 1621862400, // meta info timestamp, optional

"*dust*": "PMSx003", // dust sensor type

"*meteo*": ["BME680", "SHT31"], // more as one type present in kit

"*energy*": { "solar": "5W", "accu": "Li-Ion" }, // energy type: dflt "adaptor"

"*gps*": "NEO-6", // sensor type

"*geolocation*": { "geohash": "u1hjjnwhfn", "alt": 18.2 }, // static location

"*GeoGuess*": True, // optional if geolocation geohash is gateway location

"*event*": 13 // measurement event

}

Measurements Data Exchange Format

'net' record example



```
"net": {  
  "timestamp": 1621862950, // or "2021-05-24T13:29:10+00:00"  
  "TTN_id": "kipster-k1",  
  "TTN_app": "201802215971",  
  "type": "TTNV2",  
  "gateways": [  
    { "gateway_id": "eui-ae01c16", "rssi": -94, "snr": 9.5, "geohash": None }  
  ]  
},
```

Measurements Data Exchange Format

'data' record example



```
"data": { // measurements, only those active at that moment
  "version": 0.2, // data version, optional
  "timestamp": 1621862400, // measurement timestamp, optional
  // internal use: 'sensor type': [ ("field name", value [, unit[, calibration]] ), ...]
  "NEO-6": { "geohash": "u1hjjnwhfn", "alt": (23.2, None , [-1, 1, 0.01] ) },
  "BME680": { }, // present but undefined or invalid
  "SHT31": [ { "temp": 20.1, "rv": 70.1 }, { "temp": 20.3, "rv": None } ],
  "PMSx003": { // _cnt items are PM count up to upper bound bin!!
    "pm05_cnt": 1694.1, "pm10": 29.4, "pm25_cnt": 2396.9, "pm03_cnt": None,
    "grain": (0.5, "mu" ), // average grain size
    "pm1_cnt": 2285.7, "pm25": 20.4, "pm10_cnt": 2.4, "pm1": 13.0 },
  "accu": ( 89.5, "%" )
}
```